



SIP/Multicast Intercom Speaker

GSC3506 V2

The GSC3506 V2 is a 1-way public address SIP speaker that allows offices, schools, hospitals, apartments and more to build powerful public address announcement solutions that expand security and communication. This robust SIP speaker offers crystal clear HD audio functionality with a high-fidelity 30-Watt HD speaker. The GSC3506 V2 support built-in whitelists, blacklists and greylists to easily block unwanted calls, SIP and multicast paging, group paging and PTT. The users can easily sculpt a state-of-the-art security and PA announcement solution. Thanks to its modern industrial design and rich features, the GSC3506 V2 is the ideal SIP speaker for any setting.




Speaker with HD acoustic chamber



Features SIP paging, multicast paging, call-waiting with priority override



Full-band and wide-band audio codec support including Opus & G.722



1x 3-Pin differential line out port



1x 2-pin switch-in input port, 1x Alarm-in input port, one DC24V port, vol+/- Key, reset, 1x network port, 1x USB port



One 10/100Mbps network port with PoE/ PoE+/PoE++

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, RTCP-XR,HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, LLDP-MED, SIMPLE, LDAP,TR-069, 802.1x, TLS, SRTP, IPv6, OpenVPN®
Network Interfaces	One 10/100 Mbps port with integrated PoE/PoE+/PoE++
Auxiliary Port	One 2-pin switch-in input port, one Alarm-in input port, one differential line out port, one network port, one DC24V port, vol+/- Key, reset
USB Port	USB2.0, External USB Storage
Voice Coders and Capabilities	G.711 μ /a, G.722 (wide-band), G.726-32, iLBC, Opus, G.723, G.729A/B, in-band and out-ofband DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, PLC, AJB, AGC, ANS
Telephony Features	SIP Paging, Multicast Paging,Group Paging, PTT, Call-waiting with priority override
HD Audio	Yes, HD speaker with support for full-band audio
Speaker	30W high-fidelity HD speaker(coaxial) Frequency: 110Hz-20000 Hz Sensitivity: Up to 95 dBA at 1W power at 1 meter
QoS	Layer 2 QoS (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control,secure boot
Multi-language	English, German, French, Spanish, Portuguese, Russian & Chinese
Upgrade/Provisioning	Firmware upgrade via TFTP / HTTP / HTTPS or local HTTP upload, mass provisioning using GDMS/TR069 or AES encrypted XML configuration file
Power & Green Energy Efficiency	Integrated PoE 802.3af Class 3, PoE+ 802.3at Class 4, PoE++ 802.3bt Class 6
Temperature and Humidity	Operation: 0°C to 45°C Storage: -10°C to 60°C, Humidity: 10% to 90% Non-condensing
Package Content	GSC3506 V2, Mounting hole cut-Out template, Ceiling mount kit (optional), Quick installation guide
Physical	Unit Dimensions: 257.5mm (diameter) x 118mm (depth) Unit Weight: 2.14kg , Box Weight: 2.76kg
Compliance	FCC: FCC 47 CFR Part 15 Subpart B IC: ICES-003 CE: EN 55032:EN 55035; EN IEC 61000-3-2: EN 61000-3-3; EN IEC 62368-1. UKCA: BS EN 55032;BS EN 55035;BS EN IEC 61000-3-2;BS EN 61000-3-3;BS EN IEC 62368-1. RCM: AS/NZS CISPR 32:AS/NZS 62368.1